

Additional Configurations and Troubleshooting Guide for Linux

For Technology Coordinators

2018-2019

Published August 28, 2018

Prepared by the American Institutes for Research®



Descriptions of the operation of the Test Information Distribution Engine, Test Delivery System, and related systems are property of the American Institutes for Research (AIR) and are used with the permission of AIR.

Table of Contents

Additional Configurations and Troubleshooting for Networks & Linux Workstations.....	3
Additional Configurations for Networks	3
Required Ports and Protocols	3
Configuring Filtering Systems.....	3
Configuration for Domain Name Resolution.....	3
Configuring for Certificate Revocations.....	4
Configuring Network Settings for Online Testing	4
Configuring the Secure Browser for Proxy Servers	5
Additional Configurations for Linux.....	6
Adding Verdana Font.....	6
Disabling On-Screen Keyboard.....	6
Troubleshooting for Linux	6
Resetting Secure Browser Profiles on Linux	6
Troubleshooting Text-to-Speech	7
Using Text-to-Speech.....	7
How the Secure Browser Selects Voice Packs	7
Appendix A. URLs Provided by AIR.....	8
URLs for Non-Testing Sites.....	8
URLs for Testing Sites.....	8
TA and Student Testing Sites.....	8
Online Dictionary and Thesaurus	9

Additional Configurations and Troubleshooting for Networks & Linux Workstations

This document contains additional configurations and troubleshooting for your network and Linux workstations.

Additional Configurations for Networks

This section contains additional configurations for your network.

Required Ports and Protocols

[Table 1](#) lists the ports and protocols used by the Test Delivery System. Ensure that all content filters, firewalls, and proxy servers are open accordingly.

Table 1. Ports and Protocols for Test Delivery System

Port/Protocol	Purpose
80/TCP	HTTP (initial connection only)
443/TCP	HTTPS (secure connection)

Configuring Filtering Systems

If the school's filtering system has both internal and external filtering, the URLs for the testing sites (see URLs for Testing Sites) must be whitelisted in both filters. Please see your vendor's documentation for specific instructions. Also, be sure to whitelist these URLs in any multilayer filtering system (such as local and global layers).

Configuration for Domain Name Resolution

URLs Provided by AIR, lists the domain names for AIR's testing and non-testing applications. Ensure the testing machines have access to a server that can resolve those names.

Configuring for Certificate Revocations

AIR's servers present certificates to the clients. The following sections discuss the methods used to check those certificates for revocation.

Online Certificate Status Protocol

To use the Online Certificate Status Protocol (OCSP), ensure your firewalls allow the domain names listed in [Table 2](#). The values in the Patterned column are preferred because they are more robust.

Table 2. Domain Names for OCSP

Patterned	Fully Qualified
*.thawte.com	ocsp.thawte.com
*.geotrust.com	ocsp.geotrust.com
*.ws.symantec.com	ocsp.ws.symantec.com

If your firewall is configured to check only IP addresses, do the following:

1. Get the current list of OCSP IP addresses from Symantec. The list is available at https://www.symantec.com/content/en/us/enterprise/other_resources/OCSP_Upgrade_-_New_IP_Addresses.txt.
2. Add the retrieved IP addresses to your firewall's whitelist. Do not replace any existing IP addresses.

Configuring Network Settings for Online Testing

Local Area Network (LAN) settings on testing machines should be set to automatically detect network settings.

To set LAN settings to auto-detect on Linux machines:

1. Open **System Settings**.
2. Open **Network**.
3. Select **Network Proxy**.
4. From the **Method** dropdown, select **None**.
5. Click **X** to close **Network** window.

Configuring the Secure Browser for Proxy Servers

By default, the Secure Browser attempts to detect the settings for your network’s web proxy server. However, users of web proxies should execute a proxy command once from the command prompt. This command does not need to be added to the Secure Browser shortcut. [Table 3](#) lists the form of the command for different settings and operating systems. To execute these commands from the command line, change to the directory containing the Secure Browser’s executable file.



Note: Domain names in commands The commands in [Table 3](#) use the domains [foo.com](#) and [proxy.com](#). When configuring for a proxy server, use your actual testing domain names as listed in the section ["URLs for Testing Sites"](#) in the *Technical Specifications Manual for Online Testing*.

Table 3. Specifying proxy settings using the command line

Description	System	Command
Use the browser without any proxy	Linux	<code>./IndianaSecureBrowser.sh -proxy 0 aHR0cHM6Ly9pbi50ZHMuYWlyYXN0Lm9yZy9zdHVkZW50</code>
Set the proxy for HTTP requests only	Linux	<code>./ IndianaSecureBrowser.sh -proxy 1:http:foo.com:80 aHR0cHM6Ly9pbi50ZHMuYWlyYXN0Lm9yZy9zdHVkZW50</code>
Set the proxy for all protocols to mimic the “Use this proxy server for all protocols” of Firefox	Linux	<code>./IndianaSecureBrowser.sh -proxy 1:*:foo.com:80 aHR0cHM6Ly9pbi50ZHMuYWlyYXN0Lm9yZy9zdHVkZW50</code>
Specify the URL of the PAC file	Linux	<code>./IndianaSecureBrowser.sh -proxy 2:proxy.com aHR0cHM6Ly9pbi50ZHMuYWlyYXN0Lm9yZy9zdHVkZW50</code>
Auto-detect proxy settings	Linux	<code>./IndianaSecureBrowser.sh -proxy 4 aHR0cHM6Ly9pbi50ZHMuYWlyYXN0Lm9yZy9zdHVkZW50</code>
Use the system proxy setting (default)	Linux	<code>./IndianaSecureBrowser.sh -proxy 5 aHR0cHM6Ly9pbi50ZHMuYWlyYXN0Lm9yZy9zdHVkZW50</code>

Additional Configurations for Linux

This section contains additional configurations for Linux.

Adding Verdana Font

Some tests have content that requires the Verdana TrueType font. Therefore, ensure that Verdana is installed on Linux machines used for testing. The easiest way to do this is to install the Microsoft core fonts package for your distribution.

- Fedora—Follow the steps in the “How to Install” section of the following website: <http://corefonts.sourceforge.net/>.
- Ubuntu—In a terminal window, enter the following command to install the msttcorefonts package:
`sudo apt-get install msttcorefonts`

Disabling On-Screen Keyboard

Fedora and Ubuntu feature an on-screen keyboard that should be disabled before online testing. This section describes how to disable the on-screen keyboard.

To disable the on-screen keyboard:

1. Open **System Settings**.
2. Select **Universal Access**.
3. In the *Typing* section, toggle **Screen Keyboard** to **Off**.

Troubleshooting for Linux

This section contains troubleshooting tips for Linux.

Resetting Secure Browser Profiles on Linux

If the Help Desk advises you to reset the Secure Browser profile, use the instructions in this section.

1. Log on as a superuser or as the user who installed the Secure Browser, and close any open Secure Browsers.
1. Open a terminal, and delete the contents of the following directories:

```
/home/username/.air
```

```
/home/username/.cache/air
```

where `username` is the user account where the Secure Browser is installed. (Keep the directories, just delete their contents.)

2. Restart the Secure Browser.

Troubleshooting Text-to-Speech

Using text-to-speech requires at least one voice pack to be installed on testing computers.

A number of voice packs are available for desktop computers, and AIR researches and tests voice packs for compatibility with the Secure Browsers. Additionally, not all voice packs that come pre-installed with operating systems are approved for use with online testing. The voice packs listed at the end of this section have been tested and are whitelisted by the Secure Browser.

Using Text-to-Speech

Students using text-to-speech for the practice tests must log in using a supported Secure Browser. Students can also verify that text-to-speech works on their computers by logging in to a practice test session and selecting a test for which text-to-speech is available.



Note: We strongly encourage schools to test the text-to-speech settings before students take operational tests. You can check these settings through the diagnostic page. From the student practice test login screen, click the **Run Diagnostics** link, and then click the **Text-to-Speech Check** button.



Note: Text-to-speech tracking does not function correctly on Linux OS. If students require the use of this accommodation (TTS with tracking), they must use a different operating system.

How the Secure Browser Selects Voice Packs

This section describes how AIR's Secure Browsers select which voice pack to use.

Voice Pack Selection on Desktop Versions of Secure Browsers

When a student who is using text-to-speech starts a test, the Secure Browser looks for voice packs on the student's machine. Upon recognizing an approved voice pack, the Secure Browser uses the one with the highest priority.

If any of the approved voice packs has also been set as the default voice on the computer, then that voice pack will always get the highest priority.

Appendix A. URLs Provided by AIR

This appendix presents information about the URLs that AIR provides. Ensure your network's firewalls are open for these URLs.

URLs for Non-Testing Sites

[Table 4](#) lists URLs for non-testing sites, such as Test Information Distribution Engine, Online Reporting System, and Learning Point Navigator.

Table 4. AIR URLs for Non-Testing Sites

System	URL
Portal and Secure Browser installation files	https://indiana.portal.airast.org/
Single Sign-On System	*Will be available at a later time.
Test Information Distribution Engine	*Will be available at a later time.
Online Reporting System	*Will be available at a later time.

URLs for Testing Sites

Testing sites provide test items as well as support services such as dictionaries and thesauruses.

TA and Student Testing Sites

Testing servers and satellites may be added or modified during the school year to ensure an optimal testing experience. As a result, AIR strongly encourages you to whitelist at the root level. This requires using a wildcard.

Table 5. AIR URLs for Testing Sites

System	URL
TA and Student Testing Sites Assessment Viewing Application	*.airast.org *.tds.airast.org *.cloud1.tds.airast.org *.cloud2.tds.airast.org

Online Dictionary and Thesaurus

Some online assessments contain an embedded dictionary and thesaurus provided by Merriam-Webster. The Merriam-Webster URLs listed in [Table 6](#) should also be whitelisted to ensure that students can use them during testing.

Table 6. AIR URLs for Online Dictionaries and Thesauruses

Domain Name	IP Address
media.merriam-webster.com	64.124.231.250
www.dictionaryapi.com	64.124.231.250